


3/4 shut off valve
max 125F (55C)

1. 208V / 240V 50/60Hz 1 Phase 16Amp
2. Water drain pipe Ø25mm - 1" Max drain height 400mm
3. Water line requirements Ø3/4" max temp 125F (55C)
4. Built-in Detergent and Rinse-aid dispenser



- Tank with rounded corners.
- Control panel with 5 preset wash cycle times.
- Door with magnetic safety switch
- Useful washing height 31,5 cm, dish Ø32cm
- Square basket 50x50 cm. (supplied with 1 plate basket, 1 flat basket, 2 cutlery holders).
- Independent lower/upper washing and rinsing arms.
- Washing cycle time 60-90-120-150-180 seconds (capacity 360÷1080 pz/h).
- Display shows boiler and tank temperature.
- Warranty 2 year parts 1 year labour (see details)

- Built-in rinse-aid and detergent pump.
- Self-cleaning cycle (CLN).
- Built-in insulated boiler made in AISI 304L stainless steel.
- Boiler and tank heating through thermostatically protected armoured heating elements
- Tank capacity lt. 26 and boiler capacity lt. 8.
- Water consumption per cycle lt. 3,8 - Water pressure input 1,5-3,0 bar - Max temp of inlet water 125F (55C).
- Tank heating element kW 2,5 - Boiler heating element kW 3,0.
- Washing pump power 3/4 HP.
- Noise level at 1 mt. < 70 dbA.
- Total power kW 3,55.