

CBB60S STAINLESS STEEL BACK BAR REFRIGERATOR

Top is 1.5" thick solid foamed stainless steel.

24" depth conserves important workspace.

Standard with interior top ventilated s/s duct to allow for even temperature across all doors.

Environmentally friendly R290 Hydrocarbon gas.

Electronic thermostat with external digital LED display for accurate control located behind front access panel.

Each door is equipped with locks and magnetic gaskets that are removable for cleaning.

All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.

Easy to mount plate casters (two lockable) are standard with all units. Optional larger 5.75" casters available.




Interior LED lighting and bright stainless steel interior.


Front accessible condensing unit for easy cleaning and maintenance.

Tested to NSF Standard 7 requirements for food storage.

Standard with full two-year parts and labour warranties and a five-year compressor warranty.

Celco Model	Temperature range	Refrigerant	Number Of Doors	Number Of Shelves	Nema Plug	Current (A)	Power	Capacity (cu-ft)	Dimensions (Inches) ₩xDxH
CBB60S	33°F~41°F	R290	2	4	5-15P	3	2/5HP	14.16	61.10 x 24.41 x 36.22
61'(1551)			47.3'(120 24.4"(620))2)		•		•	







In the interest of continuous improvement, specifications are subject to change.

585 Secretariat Court, Mississauga, Ontario, L58 2A5 phone: 905-364-5200 1-866-77CELCO (23526) fax: 905-364-5205 email: info@celco.ca

www.celco.ca