

CBD48-2 DIRECT DRAW BEER COOLER

Top is 1.5" thick solid foamed stainless steel.

Electronic thermostat with digital LED display for accurate control located behind front access panel.

Self-contained capillary tube system using environmentally friendly CFC free refrigerant (R290). Front breathing.

Front accessible condensing unit for easy Cleaning and maintenance.

High-grade reinforced stainless steel coved corner floor.

External drain mount.

Easy to mount 3.25" casters (two lockable) are standard with all units.

Mounted 4-way air distributor.

Interior LED lighting.

Bright mirror finish stainless steel interior.



24" depth conserves important work space


Each door is equipped with locks and magnetic gaskets that are removable for cleaning.

Exterior cabinet construction consists of black powder coated steel/ front and sides.


Tested to NSF Standard 7 requirements for food storage.


Standard with full two-year parts and labour warranties and a five-year compressor warranty.

Celco Model	Temperature range	Refrigerant	Number Of Doors	Number Of Shelves	Nema Plug	Current (A)	Power	Capacity (cu-ft)	Dimensions (Inches)
CBD48-2	33°F~41°F	R290	2	N/A	5-15P	3	2/5HP	10.45	49.13 x 24.41 x 50.98















In the interest of continuous improvement, specifications are subject to change.