

## Technical data

### Multi-mode cabinet (R,F,IC)\*

# MONTREAL XL EC PUSH 210 (U) NAM

**R-290 110-120V/60Hz**

<b>General data</b>		<b>Refrigerator IAT**</b>	<b>Freezer IAT**</b>	<b>Ice cream freezer IAT**</b>
gross content	cu.ft.	42,28		
net content	cu.ft.	13,95	18,86	21,58
total display area (TDA)	sq.ft.	16,82		
classification acc. to 10 CFR §431 Subpart C - Commercial Refrigerators, Freezers and Refrigerator-Freezers	---	R	F	ICF
ambient temperature range	°F ... °F	61 ... 77		
adjustment temperature range	°F ... °F	+28 ... +47	-2,2 ... +8,6	-22 ... -5,8
sound pressure in 1 m distance	dB(A)	43,6		
<b>Electrical data</b>				
nominal voltage/frequency	V / Hz	110-120/60		
nominal power consumption cabinet	W	430		
nominal current	A	9,0		
fuse protection	A	15		
energy consumption (at 75,2°F)	kWh/24h	2,37	4,23	7,75
energy consumption (at 75,2°F)	BTU/24h	8087	14433	26444
length of power supply cord	inch	68,9		
<b>Refrigeration data</b>				
refrigerant type	---	R-290		
refrigerant charge	oz	4,59		
max. operating pressure	bar	30		
<b>Physical dimensions</b>				
length outside/inside	inch	85,47 / 77,68		
depth outside/inside	inch	40,43 / 33,98		
front access height/height outside	inch	33,35 / 35,83		
height inside	inch	26,38		
stacking hight (is basket height for meat cooling)	inch	11,42	15,75	17,72
net weight (excl. packaging, incl. internal accessories necessary for meat cooling)	lb	353		
gross weight (incl. packaging, incl. internal accessories necessary for meat cooling)	lb	421		

\*Multi-mode cabinet: Temperature setting from -22°F to +47°F possible,

\*\*IAT - Integrated Average Temperature

Adjustment temperature range has to be chosen according to product requirements

24.03.2021