

Technical data

Multi-mode cabinet (R,F,IC)*

MONTREAL XL PUSH 250 (U) NAM

R-290 110-120V/60Hz

General data		Refrigerator IAT**	Freezer IAT**	Ice cream freezer IAT**
gross content	cu.ft.	52,23		
net content	cu.ft.	21,90	28,08	30,12
total display area (TDA)	sq.ft	22,53		
classification acc. to 10 CFR §431 Subpart C - Commercial Refrigerators, Freezers and Refrigerator-Freezers	---	R	F	ICF
ambient temperature range	°F ... °F	61 ... 77		
adjustment temperature range	°F ... °F	+28 ... +47	-2,2 ... +8,6	-22 ... -5,8
sound pressure in 1 m distance	dB(A)	43,6		
Electrical data				
nominal voltage/frequency	V / Hz	110-120/60		
nominal power consumption cabinet	W	450		
nominal current	A	9,0		
fuse protection	A	15		
energy consumption (at 75,2°F)	kWh/24h	3,03	4,97	10,65
energy consumption (at 75,2°F)	BTU/24h	10339	16958	36339
length of power supply cord	inch	68,9		
Refrigeration data				
refrigerant type	---	R-290		
refrigerant charge	oz	4,59		
max. operating pressure	bar	30		
Physical dimensions				
length outside/inside	inch	98,54 / 93,43		
depth outside/inside	inch	40,43 / 33,98		
front access height/height outside	inch	33,31 / 35,83		
height inside	inch	28,94		
stacking height (is basket height for meat cooling)	inch	14,17	18,50	18,5 / 20,87
net weight (excl. packaging, incl. internal accessories necessary for meat cooling)	lb	489		
gross weight (incl. packaging, incl. internal accessories necessary for meat cooling)	lb	580		

*Multi-mode cabinet: Temperature setting from -22°F to +47°F possible,

**IAT - Integrated Average Temperature

Adjustment temperature range has to be chosen according to product requirements

24.08.2021